

	Fiber type	SMF ※Others (PMF, DSF, etc.) are available.		
Main Unit Type WTFM	Fiber connector	FC/SPC Xothers (SC, APC, etc.) are available.		
	Insertion Loss	≦0.7dB		
	Dimensions	L62 × W57 × H34mm (without protrusion part)		

	Center wavelength	Please specify the center wavelength range which carries out variable.(For example:1540~1560nm)				
	Tuning range	20nm				
Filter Unite Type FC	Filter type (Standard BPF) 1560nm	FWHM	Cavity	I.L	≪Others (BPF, LPF, SPF, Etalon, etc.)	
		1±0.2nm	1	≦1dB	are available.	
		3±0.3nm	1	≦0.5dB	timesThis specification is for SMF .	
		5±0.5nm	2	≦0.5dB	$ m \ref{The I.L.}$ does not include WTFM main unit's	

XSpecifications are subject to change without notice.

☆The filter is manufactured at Koshin. Please feel free to contact us for product consultation.
◇The filter cassette and the main part can be purchased separately.

Another type of main unit (TFM/FC) is also available, where only one filter cassette can be inserted.

Yamaichi Electronics Group **For Inquiries** YAMAICHI Koshin Kogaku Co., Ltd. ELECTRONIC Sales Department 69-3 Bodai Hadano-shi Kanagawa, 259-1302 **Head Office Sales Department** Japan 3-28-7 Nakamagome Ootaku Tokyo 143-8515 TEL:+81-463-75-5196 FAX:+81-463-75-3535 Japan E-mail:overseas-sales@koshin-kogaku.co.jp TEL:+81-3-3778-6155 FAX:+81-3-3778-6177 URL:http://www.koshin-kogaku.co.jp/english